

Spécial-Marché

Inox

Gamme 1655 / 1425 / 1175

Range 1655 / 1425 / 1175

Gaz

Gas

Carrosserie inox, équipé de moteurs flottants, réglables, indépendants par broches. Vitres de protection K.GLASS avec blocage à l'ouverture et à la fermeture. Compartiments techniques protégés de la graisse de cuisson et chaleur (haute température) par une double paroi démontable. Livrée avec broches cuisanpacs (Réf. CUI..., voir options et accessoires p34 à 35). Paraboles inox démontables entre les éléments de chauffe.

All stainless steel finish, with independent floating, adjustable motors, by spit. Equipped with glass protection K.GLASS, with blocking when opening and closing. Optional Interior lighting & illuminated roof. Technical compartments protected against infiltration of cooking fats and heat by a double removable panel. Stainless panels removable between burners / heating elements. Delivered with prongless spits (Ref. CUI ... see options and accessories p34 to 35).



1175.6SMiG
+ 1175PR6
Version gaz

	<ul style="list-style-type: none"> ● Puis. modèle Elec Electric model power ● Puis. modèle Gaz Gas model power 	Dimensions hors options en mm (L X P X H) Dimensions without options in mm (W X D X H)	Poids Weight	Réf.	
Rôtissoires Spécial-Marché inox. <i>Stainless steel Special-Marché rotisseries.</i>	42 kW tri 52,8 / 0,84 kW mono	1655 x 540 x 1665	300 kg	1655.8SMiG	
	38 kW tri 39,6 / 0,8 kW mono	1655 x 540 x 1285	235 kg	1655.6SMiG	
	33,1 kW tri 44 / 0,54 kW mono	1425 x 540 x 1665	225 kg	1425.8SMiG	
	30 kW tri 33 / 0,5 kW mono	1425 x 540 x 1285	170 kg	1425.6SMiG	
	25 kW tri 28 / 0,5 kW mono	1425 x 540 x 1105	150 kg	1425.5SMiG	
	20 kW tri 22 / 0,42 kW mono	1425 x 540 x 930	130 kg	1425.4SMiG	
	25,6 kW tri 40 / 0,54 kW mono	1175 x 540 x 1665	180 kg	1175.8SMiG	
	19,5 kW tri 30 / 0,44 kW mono	1175 x 540 x 1285	135 kg	1175.6SMiG	
	13,4 kW tri 20 / 0,47 kW mono	1175 x 540 x 930	90 kg	1175.4SMiG	
			Capacité volailles Capacity chickens		



1175.6SMiG
Version gaz



1425.8SMiG
+ 1425SR
Version gaz