

DESIGN & PERFORMANCE

The Roti Roaster offers a perfect blend of durability and performance. It comes in two configurations: **Standard (front door only)** and **Pass-Through (front and rear door)**, providing flexibility for your space. The unit's energy-efficient K.Glass doors help reduce operating costs while enhancing thermal efficiency. The intuitive Touch Control Panel simplifies recipe management and guarantees reliable cooking outcomes.

An **optional ventless hood** with powerful dual filtration system (removable and washable stainless-steel grease filter and activated carbon filter). This makes the Roti Roaster adaptable for indoor use. The **integrated cooking drip pan** captures flavorful juices, while allowing you to cook vegetables and side dishes alongside rotisserie items, improving both efficiency and ingredient utilization. The **integrated pull-out table** provides a convenient and space-saving solution for food preparation.



**FBP5.560
Standard**

SPECIFICATIONS

	FBP5.560	FBP8.560	FBP8.760	FBP16.560	FBP16.760
Power	6kW, 15 Amps 208-240v/60Hz/3-ph	7.5kW, 18 Amps 208-240v/60Hz/3-ph	9.5kW, 23 Amps 208-240v/60Hz/3-ph	15kW, 37 Amps 208-240v/60Hz/3-ph	19kW, 48 Amps 208-240v/60Hz/3-ph
Baskets incl.	5	8	8	16	16
Capacity (chickens)	15-20	24-32	32-40	48-64	64-80
Dim. (HxWxD) Countertop	30 x 34 7/8 x 32 1/8"	35 1/2 x 34 7/8 x 34 7/8"	35 1/2 x 42 3/4 x 34 7/8"		
Dim. (HxWxD) Floor Standing	67 3/4 x 34 7/8 x 32 1/8" (with optional cabinet)	73 3/8 x 34 7/8 x 34 7/8" (with optional cabinet)	73 3/8 x 42 3/4 x 34 7/8" (with optional cabinet)	78 x 34 7/8 x 34 7/8" (double-stacked)	78 x 42 3/4 x 34 7/8" (double-stacked)
Weight	364 lbs	419 lbs	496 lbs	838 lbs	992 lbs
Packed Weight	474 lbs	529 lbs	607 lbs	1,058 bs	1,214 lbs
Cleaning	manual cleaning				
Warranty	1 year on parts and labor (glass door excluded)				

TECHNICAL CHARACTERISTICS

- Energy-efficient heating element
- Fully insulated with rock wool (Bio-soluble aluminum encapsulation)
- K.Glass thermal double glazing mounted on silicone seal (anti-scald front panel)
- Bakelite ¼ turn heat resistant locking door handle
- Halogen lighting
- Automatic cooling of heating turbines after switch off (safety of technical components)
- Integrated drip pan (multi functioning for cooking vegetables and more)
- Delivered with cooking baskets (BALD560/760)
- Automatic hold cycle up to 2 hours after cooking is completed



**FBP8.760
Passthrough**

ENERGY & COST-EFFICIENT K-GLASS

Featuring insulated, double-glazed K-GLASS doors, the Roti Roaster is engineered for optimal energy efficiency. The inner pane has a specialized thin metal coating that regulates heat transfer, offering exceptional resistance to thermal radiation. This design enhances energy efficiency, lowering operational costs and contributing to significant savings. The glass also minimizes heat emission in the kitchen, improving comfort for your team, and enhances safety by preventing burns upon contact with the door surfaces.

STACKABLE OPTIONS

Maximize Space and Efficiency

Our stackable Roti Roaster units **FBP16.760** and **FBP16.560** are designed for versatility and convenience in high-demand kitchens. These models provide a compact and efficient way to cook multiple items simultaneously, increasing your throughput while saving valuable space.



FBP16.560
Stackable & Passthrough

TOUCH CONTROL PANEL



- 5-inch colored touchscreen control panel
- 4 categories of pre-recorded programs
- Time and temperature programming
- 99 programmable recipes

ACCESSORIES

included:

BALD560/760
Basket for poultry

optional:

PD560/760
Vegetable tray

BAP560/760
Small cuts basket


PLC560/760
Cooking basket

BAB560/760
Cooking spit

CAP5.560/8.560/8.760
Ventless hood for indoor use, equipped with removable and activated carbon filter



COMING SOON!



Rotisol USA

21618 Marilla St, Chatsworth, CA 91311, United States
info@rotisolusa.com – Phone: (310) 671- 7254

Origine / Origin
Europe

